LUBRHOPHOS® LP 700

TECHNICAL DATA SHEET NA 90002022 - MARCH 2021

THIS PRODUCT SOLD BY:

Azelis L&MF US

154 Pioneer Drive, Leominster, MA 01453
(978) 534-1425 Fax (978)840-1060

IDENTIFICATION

Chemical Name: POLYETHYLENE PHENYL ETHER PHOSPHATE

SPECIFICATIONS	RESULTS	METHOD
Moisture (Karl Fisher), %	1.0 Max	RP-0327
Color Gardner	4 Max	RP-0138
Appearance (25°C)	Clear to Slightly Hazy Viscous Liquid	RP-0064
Acid Number (KOH to First INFL. PT.), mgKOHg	96.0 – 107.0	RP-0427
Nonionic Content. %	7.0 Max	RP-0351

STANDARD APPLICATIONS

LUBRHOPHOS® LP 700 is an anti-wear agent and corrosion inhibitor used in water-based synthetix metalworking fluids. Low foaming hydrotrope for metal cleaning fluid.

STANDARD PACKAGING

LUBRHOPHOS® LP 700 is available in Bulk Quantities, and 540 LB. Closed Head Steel Drums. Alternative package sizes may be available upon request.

SHELF LIFE

LUBRHOPHOS® LP 700 has a shelf life of 730 days.

WARNING

The information contained in this document is given in good faith and based on our current knowledge. It is only an indication and is in no way binding, notably as regards infringement of or prejudice to third parties through the use of our products. SOLVAY GUARANTEES THAT ITS PRODUCTS COMPLY WITH ITS SALES SPECIFICATIONS.

This information must on no account be used as a substitute for necessary prior tests which alone can ensure that a product is suitable for a given use. Users are responsible for ensuring compliance with local legislation and for obtaining the necessary certifications and authorisations. Users are requested to check that they are in possession of the latest version of the present document and SOLVAY is at their disposal to supply any additional information.



For orders or questions, call us at the following numbers or visit us at www.solvay.com